

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

TREND Underhållsvax

Product no.

160411, 160413

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Treatment wax

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Gipeco AB, Box 3035
550 03 Jönköping
Telefon: 036-18 19 00

Contact person

-

E-mail

info@gipeco.se

SDS date

2015-12-29

SDS Version

2.0

1.4. Emergency telephone number

Use your national or local emergency number
See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This product is not classified as dangerous.
See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)

-

Signal word

-

Hazard statement(s)

-

Safety statement(s)	General	-
	Prevention	-
	Response	-
	Storage	-
	Disposal	-

Identity of the substances primarily responsible for the major health hazards

-

2.3. Other hazards

▼ Additional labelling

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. (EUH210)

Additional warnings

-

VOC

-

SECTION 3: Composition/information on ingredients

▼ 3.1/3.2. Substances/Mixtures

NAME: ammonia ...%
 IDENTIFICATION NOS.: CAS-no: 1336-21-6 EC-no: 215-647-6 REACH-no: 01-211948876-14 Index-no: 007-001-01-2
 CONTENT: <0.1%
 CLP CLASSIFICATION: STOT SE 3, Skin. Corr. 1B
 H314, H335

NAME: 2-dimethylaminoethanol N,N-dimethylethanolamine
 IDENTIFICATION NOS.: CAS-no: 108-01-0 EC-no: 203-542-8 Index-no: 603-047-00-0
 CONTENT: <0.1%
 CLP CLASSIFICATION: Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, STOT SE 3, Skin Corr. 1B
 H226, H302, H312, H314, H331, H335
 NOTE: S

NAME: triethylamine
 IDENTIFICATION NOS.: CAS-no: 121-44-8 EC-no: 204-469-4 Index-no: 612-004-00-5
 CONTENT: <0.1%
 CLP CLASSIFICATION: Flam. Liq. 2, Acute Tox. 4, STOT SE 3, Skin corr. 1A
 H225, H302, H312, H314, H332, H335
 NOTE: S

NAME: 1,2-benzisothiazol-3(2H)-one
 IDENTIFICATION NOS.: CAS-no: 2634-33-5 EC-no: 220-120-9 Index-no: 613-088-00-6
 CONTENT: <0.05%
 CLP CLASSIFICATION: Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1
 H302, H315, H317, H318, H400

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent

Other informations

ATEmix(inhale, vapour) > 20
 ATEmix(dermal) > 2000
 ATEmix(oral) > 2000

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting

unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Not applicable

▼ 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may cause an allergic reaction in people who are already so disposed.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

No special

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original.

▼ Storage temperature

Does not withstand frost.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

▼ OEL

triethylamine (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 2 ppm | 8 mg/m³

Short-term exposure limit (15-minute reference period): 4 ppm | 17 mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

2-dimethylaminoethanol N,N-dimethylethanolamine (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 2 ppm | 7.4 mg/m³

Short-term exposure limit (15-minute reference period): 6 ppm | 22 mg/m³

▼ DNEL / PNEC

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Smoking, consumption of food or liquid, and storage of tobacco, food or liquid, are not allowed in the workroom.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

-

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements.

Skin protection

No specific requirements.

Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type.

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Liquid	White	Faint	9,1	-	-

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-	-	-

Explosion limits (Vol %)	Oxidizing properties
-	-

▼ Solubility

Solubility in water	n-octanol/water coefficient	pH Use solution
Soluble	-	8,4 (1%)

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

According to EC-Regulation 1907/2006 (REACH)

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

▼ Acute toxicity

Substance	Species	Test	Route of exposure	Result
1,2-benzisothiazol-3(2H)-one	Rat	LD50	Dermal	4115 mg/kg
1,2-benzisothiazol-3(2H)-one	Rat	LD50	Oral	1193 mg/kg
2-dimethylaminoethanol N,N-d...	Rat	LD50	Oral	1187 mg/kg
2-dimethylaminoethanol N,N-d...	Rat	LC50	Inhalation	6,1 mg/l/4h
ammonia%	Mouse	LD50	Oral	350 mg/kg

▼ Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

▼ Long term effects

This product contains substances that may cause an allergic reaction in people who are already so disposed.

SECTION 12: Ecological information

▼ 12.1. Toxicity

Substance	Species	Test	Test duration	Result
1,2-benzisothiazol-3(2H)-one	Fish	LC50	96 h	2,18 mg/l
1,2-benzisothiazol-3(2H)-one	Daphnia	EC50	48 h	2,94 mg/l
1,2-benzisothiazol-3(2H)-one	Algae	ErC50	72 h	0,11 mg/l
2-dimethylaminoethanol N,N-d...	Fish	LC50	96h	146,63 mg/l
2-dimethylaminoethanol N,N-d...	Daphnia	EC50	48h	98,37 mg/l
2-dimethylaminoethanol N,N-d...	Algae	IC50	72h	34,47
ammonia%	Fish	LC50	96h	0,75-3,4 mg/l
ammonia%	Daphnia	EC50	48h	24 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC

No data available.

▼ **12.4. Mobility in soil**

1,2-benzisothiazol-3(2H)-one: Log Koc= 1,10787, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains ecotoxic substances which can have damaging effects on water-organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

This product is not covered by the regulations on dangerous waste.

Waste

EWC code

16 10 02

Specific labelling

-

Contaminated packing

No specific requirements.

SECTION 14: Transport information

Not listed as dangerous goods under ADR and IMDG regulations.

14.1 – 14.4

ADR/RID

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

Notes

Tunnel restriction code

IMDG

UN-no.

Proper Shipping Name

Class

PG*

EmS

MP**

Hazardous constituent

▼ **IATA/ICAO**

UN-no.

Proper Shipping Name

Class

PG*

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

Sources

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H226 - Flammable liquid and vapour.

H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H331 - Toxic if inhaled.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

H400 - Very toxic to aquatic life.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2

-

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

YT

Date of last essential change (First cipher in SDS version)

2015-08-19

Date of last minor change (Last cipher in SDS version)

2015-08-19